



# SINGLE DOOR UPRIGHT REFRIGERATORS



## Medium Temperature Merchandising Solutions

*You know it's cold when it's Minus Forty®*


### GREAT FEATURES. OUTSTANDING VALUE.



Brilliant, energy efficient LED lighting creates an impressive visual impact and last far longer than fluorescent lights. Standard on all models.



Medium temperature system range from as low as 32°F up to 50°F. Ideal product temperature can be pre-programmed to suit your storage needs.



Energy efficient, triple pane, heat reflective Low-e glass door provides superior insulation while innovative warm edge technology eliminates heat from the glass.



Captivating LED backlit translight display provides superior branding and sales potential. Custom cabinet graphics are also available.



Maintenance free condenser\* helps maintain the cooler's performance while eliminating the need for costly, regular cleaning.



Programmable Electronic Control Center provides "real time" information with audible and visual alarms. Standard on all models.

## Standard Features

- Available in Black or White. Custom colors available (some conditions may apply).
- High Intensity Interior LED Lighting Eliminates Bulb Replacement
- Extra Thick 2½" Insulated Walls for Maximum Efficiency
- Triple Pane Tempered Glass Door for Maximum Insulation
- Maintenance Free Condenser\* Design
- Electronic Digital Control Center with Continuous Temperature Display
- High Temperature and Door Open Alarms with Visual Messages
- Self Closing, Torsion Bar Door
- Stainless Steel Interior Bottom
- Forced Air for Quick Cooling
- Adjustable, Coated White Shelves
- Fully Automatic Frost Free Operation
- Ozone-Friendly R134a CFC Free Refrigerant
- All Interior Corners 3/8" (1cm) Radius
- Bottom Mount Compressor/Condenser
- Durable White Baked Enamel Galvanized Steel Interior
- Tough Baked Enamel Galvanized Steel Exterior
- Snap-In Door Gasket for Easy Cleaning
- 24/7 Customer Care Support

## Specifications

Models 13-USGR-X1, 19-USGR-X1 and 22-USGR-X1 are certified for use with both potentially hazardous and non-potentially hazardous packaged foods. All other models certified for use with non-potentially hazardous packaged foods.



Certified to Energy Standards:  
U.S. Department of Energy (DOE)  
California Energy Commission  
Natural Resources Canada (Nrcan)



Model	09-USGR-X1 09M-USGR-X1 09X-USGR-X1	10-USGR-X1	13-USGR-X1	19-USGR-X1	22-USGR-X1
Style	Low Profile	Low Profile	Mid Size	High Capacity	High Capacity
Standard Cabinet Color	Black or White	Black or White	Black or White	Black or White	Black or White
Capacity (cubic feet)	8.5 / 7.3 / 5.9	9.8	12.0	18.53	22.7
Capacity (liters)	241 / 207 / 167	278	340	524.7	643
Temperature °F	50 to 32	50 to 32	50 to 32	50 to 32	50 to 32
Temperature °C	10 to 0	10 to 0	10 to 0	10 to 0	10 to 0
Height (inches)	54	54	62	79	79
Height (cm)	137	137	158	200	200
Width (inches)	23.75	26.5	26.5	26.5	30
Width (cm)	60.3	67.3	67.3	67.3	76.2
Depth less handle (inches)	26.53 / 23.28 / 19.78	26.21	27.47	32.97	32.97
Depth less handle (cm)	67.38 / 59.13 / 50.24	66.57	69.8	83.7	83.7
Interior LED Light Strips	2	2	2	2	2
LED Translight Display	-	-	Yes	Yes	Yes
Adjustable Shelves	3	3	3	4	4
Bottom Shelf	1	1	1	1	1
Casters	Yes	Yes	Yes	Yes	Yes
Volts / Hz / Phase	115 / 60 / 1	115 / 60 / 1	115 / 60 / 1	115 / 60 / 1	115 / 60 / 1
Amps	2.9	2.9	2.9	4.9	4.9
H.P. ( kW )	1/8 ( 0.10 )	1/8 ( 0.10 )	1/6 ( 0.13 )	1/3 ( 0.25 )	1/3 ( 0.25 )
Refrigerant	R134a	R134a	R134a	R134a	R134a
Net Weight (lbs)	210 / 210 / 176	230	245	278	340
Net Weight (kg)	95.3 / 95.3 / 79.8	104.3	111.1	126.1	154.4
NEMA Configuration	5-15P	5-15P	5-15P	5-15P	5-15P


Warranty is a limited warranty, please refer to detailed warranty outline available from our Customer Care Department. Self cleaning maintenance free condenser not tested in all environments, some extreme installations may require periodic inspection and/or cleaning. All models available in 230V configuration. Specifications are subject to change without notice. Weights and dimensions do not include packaging or shipping materials.

\*Regular cleaning and maintenance not required under normal operating conditions. Some exceptions may apply. Contact Minus Forty for more information.


## Accessories for branding, promotion, customizing packout




Customized Graphics



Wire Baskets and Dividers



Wire Baskets



Wire Shelves, Menu Strips



Security Lock Assembly

Minus Forty Technologies Corp., 30 Armstrong Ave. Georgetown, Ontario Canada L7G 4R9

TEL 800.800.5706 • 905.702.1441 • FAX 905.702.1442 • www.MINUSFORTY.com

© 2015 All Rights Reserved. Minus Forty® is a registered trademark of Minus Forty Technologies Corp.